

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : A61B 17/16, B23C 5/20	A2	(11) International Publication Number: WO 99/47051 (43) International Publication Date: 23 September 1999 (23.09.99)
--	----	---


(21) International Application Number: PCT/US99/05951  
(22) International Filing Date: 18 March 1999 (18.03.99)  
(30) Priority Data:  
09/040,861 18 March 1998 (18.03.98) US  
(71)(72) Applicants and Inventors: FISHBEIN, Meyer [US/US];  
34725 Mission Hills Drive, Rancho Mirage, CA 92270 (US).  
WHITE, Patrick, Michel [US/US]; 509 Commerce Street,  
Franklin Lakes, NJ 07417 (US).  
(74) Agents: CHIATALAS, John, L. et al.; Trademark & Patent  
Counselors of America, P.C., 19th floor, 915 Broadway,  
New York, NY 10010-7108 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG,  
BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB,  
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK,  
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,  
SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA,  
ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ,  
UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD,  
RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI  
patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR,  
NE, SN, TD, TG).

**Published**

*Without international search report and to be republished  
upon receipt of that report.*

(54) Title: HOLLOW DOME REAMER WITH REMOVABLE TEETH



(57) Abstract

The surgical reamer (20) has a hollow dome (24) with apertures (26) spaced apart arranged in arcs (28) extending from an apex (30) of the dome to the base portion (32) of the dome, and removable teeth (22) positioned in the apertures. Each cutting tooth (22) has a flange (52) that is aligned flush with the external surface of the dome (24), and a raised cutting edge (50) extending above the flange and the external surface (36) of the dome, and an interior passageway (39) communicating between the outside and inside of the dome. In one embodiment, a base plate (56) is removably secured on the base portion (32) of the dome (24) to provide closure of the central cavity (34) of the dome.